

Method of blasting multiple layers or levels of rock

Publication number: AU2009202695 (A1)

Publication date: 2009-07-23

Inventor(s): BRENT GEOFFREY; GOSWAMI TAPAN +

Applicant(s): ORICA EXPLOSIVES TECH PTY LTD +

Classification:






- international: *F42D1/02; F42D1/08; F42D3/04; F42D1/00; F42D3/00*

- European: *F42D1/055; F42D3/04*

Application number: AU20090202695 20090702

Priority number(s): AU20040293486 20041013; AU20090202695 20090702;
AU20030906600 20031128

Also published as:

 AU2009202695 (A2)
 WO2005052499 (A1)
 ZA200603868 (A)
 US2007272110 (A1)
 MXPA06005935 (A)

[more >>](#)

Abstract not available for AU 2009202695 (A1)

Abstract of corresponding document: **WO 2005052499 (A1)**

A method of blasting plural layers of material (3 8, 40, 42, 44) in a blastfield (16) that reduces the amount of mechanical excavation required to expose a lower layer of material. The method includes using rows of equally spaced blastholes (18, 20, 22, 24) that pass through all of the layers and additional intermediate rows of blastholes (26, 28) that pass down only through top layer (40). Each blasthole is capped with stemming material and includes one or more decks of explosives material (46) and detonators (48), with air decks or inert stemming (45) separating adjacent explosives decks (46). The detonators in layer (40) are detonated first in order from row (18) rearwards to throw a substantial amount of the blast material from layer (40) forwardly of free face (12) onto floor (34). In the same blasting cycle and within seconds of the throw blast, explosives material in layers (42, 44) is detonated in a stand-up blast in which material in layers (38, 42, 44) is broken up but otherwise minimally displaced or thrown forwardly. Layers (38, 44) may be coal seams which are separated by interburden layer (42) and covered by overburden layer (40).

Data supplied from the **espacenet** database — Worldwide

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 2004293486 B2

(54) Title
Method of blasting multiple layers or levels of rock

(51) International Patent Classification(s)
F42D 1/02 (2006.01) F42D 3/04 (2006.01)
F42D 1/08 (2006.01)

(21) Application No: 2004293486 (22) Date of Filing: 2004.10.13

(87) WIPO No: WO05/052499

(30) Priority Data

(31) Number (32) Date (33) Country
2003906600 2003.11.28 AU

(43) Publication Date: 2005.06.09
(44) Accepted Journal Date: 2009.04.02

(71) Applicant(s)
Orica Explosives Technology Pty Ltd

(72) Inventor(s)
Brent, Geoffrey; Goswami, Tapan

(74) Agent / Attorney
Davies Collison Cave, 1 Nicholson Street, Melbourne, VIC, 3000

(56) Related Art
SU 976751
US 6520591
AU 199919653